

## Roulement conique 2984-2925-TIMKEN - 2984-2925-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/2984-2925-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> K	Factor <sup>(3)</sup> Y	Dynamic <sup>(1)</sup> C <sub>0</sub>	Factor <sup>(3)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N			N		N			
46.037	87.312	26.988	3250	2.25	1.73	3420	14300	1.68	11700	2984	2925
1.8125	3.4375	1.0625	21000			540	3225		2000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	A <sub>3</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				lb
26.988	22.225	-4.4	3.5	52.8	58.8	2.3	81.8	75.8	1.7	1.1	36.2	15.7	0.9832	6.88
1.0625	0.8750	-0.25	0.14	2.05	2.31	0.09	3.19	2.95	0.07	0.05				1.50

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952314990
Diam. intérieur	46.037 mm
Diam. extérieur	87.312 mm
Épaisseur	26.988 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE