

## Roulement conique 658-652-TIMKEN - 658-652-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/658-652-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> Y	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> X	Static <sup>(5)</sup> C <sub>0</sub>	Inner	Outer		
mm	mm	mm	N		N		N				
74.612	152.400	41.275	247000	2.41	1.47	64000	40800	1.43	270000	008	052
2.9375	6.0000	1.6250	55500			14400	10100		75300		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage		Geometry Factors			kg					
Width B	Width C	ER. Dr. μm	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(2)</sup>		G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm				kg		
41.275	31.750	-3.8	3.5	86.8	82.8	3.3	141.8	136.8	4.5	2.1	136.6	27.3	0.9918	3.42
1.6250	1.2500	-0.31	0.14	3.39	3.32	0.13	5.55	5.28	0.17	0.08			7.55	

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952321318
Diam. intérieur	74.612 mm
Diam. intérieur	2 15/16" inch
Diam. extérieur	152.4 mm
Diam. extérieur	6" inch
Epaisseur	41.275 mm
Epaisseur	1 5/8" inch
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE