

## Roulement conique 862-853-TIMKEN - 862-853-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/862-853-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>02</sub>	Factor <sup>(4)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
95.000	190.000	57.000	42000	3.30	119000	68000	1.74	63000	862	
3.742	7.480	2.244	10300		28700	15300		142000	862	

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>	A <sub>3</sub> <sup>(6)</sup>				kg	
57.000	48.000	-15.2	0.4	108.0	120.0	3.0	174.3	170.0	0.5	0.7	264.1	44.0	0.1072	7.35
2.200	1.889	-0.60	0.25	4.25	4.72	0.12	6.86	6.69	0.22	0.03				16.22

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952323589
Diam. intérieur	95 mm
Diam. intérieur	3.74" inch
Diam. extérieur	190 mm
Diam. extérieur	7.48" inch
Epaisseur	57 mm
Epaisseur	2.244" inch
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE