

## Roulement conique 687-674-TIMKEN - 687-674-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/687-674-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings					Part Number			
Bore d	O.D. D	Width T	Dynamic <sup>1)</sup> C <sub>1</sub>	Factor <sup>2)</sup> Y	Dynamic <sup>3)</sup> C <sub>2</sub>	Factor <sup>4)</sup> K	Static C <sub>0</sub>	Inner	Outer		
mm	mm	mm	N		N		N				
101.600	171.450	41.275	20500	2.47	1.28	6800	95300	1.24	38000	687	674
4.0200	6.7500	1.6265	19500			15400	12900		85700		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
Width B	Width C	ER. Dr. α <sup>5)</sup>	Max Shaft Fillet Radius R <sup>6)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>7)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>8)</sup>	A <sub>2</sub> <sup>9)</sup>	Cage				A <sub>1</sub> <sup>10)</sup>	A <sub>2</sub> <sup>11)</sup>
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			
41.275	98.902	-2.8	3.5	112.0	118.0	3.3	160.0	150.0	4.5	2.1	162.5	37.3	0.1056	3.54
1.6250	1.1875	-0.11	0.14	4.41	4.65	0.13	6.30	5.91	0.19	0.08				7.81

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952324197
Diam. intérieur	101.6 mm
Diam. extérieur	171.45 mm
Épaisseur	41.275 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE