


# Roulement conique

## M241547-M241510-TIMKEN - M241547-M241510-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/m241547-m241510-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> K	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> K	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
203.200	292.100	57.945	60000	3.33	15000	86500	1.76	117000	M241547	M241510
8.0000	11.5000	2.2813	130000		20000	19900		263000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Min. Shaft Fillet Radius R <sub>f1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sub>1</sub> <sup>(2)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(4)</sup>				A <sub>3</sub> <sup>(5)</sup>	
57.945	46.696	-4.8	3.5	217.0	221.0	3.3	276.0	272.0	4.7	2.8	0.541	127.9	0.1279	12.06
2.2813	1.8125	-0.19	0.14	8.54	8.73	0.13	10.98	10.71	0.18	0.08				26.58

## CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952327129
Diam. intérieur	203.2 mm
Diam. extérieur	292.1 mm
Épaisseur	57.945 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE