

Roulement conique

LM772748-LM772710-TIMKEN - LM772748-LM772710-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/lm772748-lm772710-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
|--------------------|---------|---------|--|----------------------------|--|----------------------------|--------------------------|-------|-------------|----------|----------|
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ Y | Dynamic ⁽³⁾ C ₂ | Factor ⁽⁴⁾ X | Static C ₀ | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 488.950 | 634.873 | 84.138 | 180000 | 1.47 | 1.27 | 40200 | 29000 | 1.24 | 267000 | LM772748 | LM772710 |
| 18.200 | 24.950 | 3.3125 | 418000 | | 108000 | | 87000 | | | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight |
|--------------------|---------|--------------------------|--|---|--|---|-------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|
| Shaft | | | | | Housing | | | | | Cage | | | |
| Width B | Width C | ER. Dr. α ⁽¹⁾ | Max. Shaft Fiber Radius r ₁ | Backing Shoulder Dia. d ₁ , d ₂ | Max. Housing Fiber Radius r ₂ | Backing Shoulder Dia. D ₁ , D ₂ | A ₁ ⁽²⁾ | A ₂ ⁽³⁾ | A ₃ ⁽⁴⁾ | G ₁ | G ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | mm |
| 84.138 | 61.912 | 46.9 | 6.4 | 510.0 | 522.8 | 3.3 | 613.3 | 600.0 | 16.2 | 3.8 | 0.40 | 0.12 | 6423 |
| 3.3125 | 2.4375 | 1.81 | 0.25 | 20.08 | 20.55 | 0.13 | 24.15 | 23.82 | 0.40 | 0.12 | | | 141.61 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952330716 |
| Diam. intérieur | 488.95 mm |
| Diam. extérieur | 634.873 mm |
| Épaisseur | 84.138 mm |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE