

## Roulement conique 32030X-TIMKEN - 32030X-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/32030x-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(1)</sup> Y	Dynamic <sup>(2)</sup> C <sub>0</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N		N			
150.000	225.000	48.000	440000	0.44	119000	10100	1.27	730000	32030K	
5.9000	8.8500	1.8800	59500		23800	25300		164000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Backing Fillet Radius r <sup>(1)</sup>	Max Housing Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Backing Fillet Radius r <sup>(2)</sup>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>2</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
48.000	36.000	1.0	3.0	163.0	100.0	2.5	317.0	206.0	2.0	4.0	407.0	114.0	0.1014	6.30
1.8800	1.4173	0.04	0.12	6.42	3.93	0.10	12.48	8.11	0.11	0.16				14.08

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952354057
Diam. intérieur	150 mm
Diam. extérieur	225 mm
Épaisseur	48 mm
Poids	6380 g
Conditionnement	1
Norme	Sans norme

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE