

Roulement conique 13889-13835D-TIMKEN - 13889-13835D-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/13889-13835d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDD

TYPE TDD

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|--------|---------|---------------------------|-------------------------|-----------------------|-----------------------|----------------|-------------------------|-----------------|----------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic C ₁₀ | Factor Y ₁ | Factor Y ₂ | C ₀ | Dynamic C ₉₀ | C ₅₀ | Factor K | |
| mm | mm | mm | mm | N | | | N | N | N | | |
| 38.100 | 63.500 | 38.100 | 31.750 | 42800 | 0.25 | 1.35 | 2.90 | 2940 | 4170 | 12300 | |
| 1.500 | 2.500 | 1.500 | 1.2500 | 10500 | | | | 190 | 270 | 2700 | |

| Part Number | | Shaft | | | | Housing | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|--------|--|--------------------------------------|--|--------------------------------------|----------------|----------------|----------------|----------------|----------------|------------------|--|------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R _{fn} | Backing Shoulder Dia. d _s | Max. Housing Fillet Radius r _{fn} | Backing Shoulder Dia. D _s | K _α | K _β | G ₁ | G ₂ | C ₁ | C ₂ | | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | mm | |
| 13889 | 13835D | 1.5 | 45.0 | 0.4 | 60.0 | - | - | 14.8 | 22.3 | 0.901 | 0.92 | | 0.30 | |
| | | 0.06 | 1.77 | 0.02 | 2.38 | | | | | | | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952355184 |
| Diam. intérieur | 38.1 mm |
| Diam. extérieur | 63.5 mm |
| Épaisseur | 38.1 mm |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE