

Roulement conique 365A-363D-TIMKEN - 365A-363D-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/365a-363d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|--------|---------|---------------------------|-------------------------|-----------------------|-----------------------|----------------|-------------------------|-----------------|----------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic C ₁₀ | Factor Y ₁ | Factor Y ₂ | C ₀ | Dynamic C ₉₀ | C ₅₀ | Factor K | |
| mm | mm | mm | mm | N | | | N | N | N | | |
| 41.275 | 90.000 | 50.010 | 42.810 | 17700 | 0.32 | 2.11 | 3.14 | 26400 | 14400 | 40000 | |
| 1.6210 | 3.5433 | 1.9689 | 1.6893 | 3950 | | | | 5930 | 3250 | 10300 | |

| Part Number | | Shaft | | | | Housing | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|-------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|--|------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | C ₂ | | | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | mm | |
| 365A | 363D | 3.5 | 55.0 | 0.8 | 84.0 | - | - | 33.8 | 14.0 | 0.0770 | 1.40 | | | 3.11 | |
| | | 0.14 | 2.17 | 0.05 | 3.31 | | | | | | | | | | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952355726 |
| Diam. intérieur | 41.275 mm |
| Diam. extérieur | 90 mm |
| Épaisseur | 50.01 mm |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE