

Roulement conique 560-552D-TIMKEN - 560-552D-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/560-552d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|-------------------------|-----------------------|-----------------------|----------------|-------------------------|-----------------|----------|--|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic C ₁₀ | Factor Y ₁ | Factor Y ₂ | C ₀ | Dynamic C ₉₀ | C ₅₀ | Factor K | |
| mm | mm | mm | mm | N | | | N | N | N | | |
| 66.675 | 123.825 | 79.375 | 63.500 | 29600 | 0.25 | 1.35 | 2.00 | 9800 | 34700 | 102000 | |
| 2.6250 | 4.8750 | 3.1250 | 2.5000 | 8850 | | | | 13000 | 7810 | 22900 | |

| Part Number | | Shaft | | | | Housing | | | | Pin | | | Geometry Factors | | | Bearing Weight |
|-------------|-------|--|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|----------------|----------------|----|------------------|----|------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R _{fs} | Backing Shoulder Dia. d _s | Max. Housing Fillet Radius r _h | Backing Shoulder Dia. D _s | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | C ₂ | | | | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | |
| 560 | 552D | 3.5 | 94.0 | 1.5 | 115.0 | - | - | 91.0 | 21.1 | 0.1100 | | | | | 3.89 | |
| | | 0.14 | 3.31 | 0.06 | 4.53 | | | | | | | | | | 8.59 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952357195 |
| Diam. intérieur | 66.675 mm |
| Diam. extérieur | 123.825 mm |
| Épaisseur | 79.375 mm |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE