


## Douille à aiguilles TA7030-Z-IKO - TA7030-Z-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/douille/ta7030-z-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**



Shaft dia. mm	Identification number								Grease retained Mass (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g		
70	TA	7030 Z	220	—	—	—	—	—	—	—

Boundary dimensions mm				Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring
F <sub>w</sub>	D	C	f <sub>2</sub> Max.	Shaft dia. d		Housing bore dia. D <sub>1</sub>		N <sub>1</sub> Min.	N <sub>2</sub> Max.	N	N	rpm	IRT 6030
				Max.	Min.	Max.	Min.						
70	82	30	3.4	70.000	69.981	82.022	81.987	—	—	70 900	159 000	3 500	IRT 6030

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952357539
Diam. intérieur	70 mm
Diam. extérieur	82 mm
Épaisseur	30 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE