

## Roulement conique 685-672D-TIMKEN - 685-672D-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/685-672d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDD

**TYPE TDD**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup> C <sub>10</sub>	Factor <sup>(2)</sup> Y <sub>1</sub>	Factor <sup>(2)</sup> Y <sub>2</sub>	Dynamic <sup>(3)</sup> C <sub>90</sub>	Factor <sup>(3)</sup> C <sub>90a</sub>	Factor <sup>(3)</sup> C <sub>90b</sub>	Factor <sup>(3)</sup> K	
mm	mm	mm	mm	N			N	N	N		
98.425	168.275	92.075	69.800	401000	0.47	1.43	2.14	88600	93300	119000	
3.8750	6.6250	3.6250	2.7500	134000				13400	12400	20900	

  

Part Number		Shaft				Housing				Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>fs</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max. Housing Fillet Radius r <sub>h</sub>	Backing Shoulder Dia. D <sub>s</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>				kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
685	672D	3.5 0.14	116.8 4.57	8.8 0.55	168.8 6.68	-	-	182.5	37.3	0.1056					7.85 17.28

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952358819
Diam. intérieur	98.425 mm
Diam. extérieur	168.275 mm
Épaisseur	92.075 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE