


## Douille à aiguilles YBH108-IKO - YBH108-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/douille/ybh108-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g	
15.875 ( $\frac{5}{8}$ )	—	—	—	—	—	—	—	—	YBH 108 15.3	
Boundary dimensions mm(inch)		Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup>	Assembled inner ring		
F <sub>w</sub>	D	C	b <sub>2</sub>	Shaft dia. h8	Housing bore dia. J7	N	N	rpm	IRB 68-1	
15.875 / $\frac{5}{8}$	22.225 / $\frac{7}{8}$	12.70 / 500	—	15.875 Max.	15.864 Min.	22.237 Max.	22.216 Min.	15 000	22 400	9 500

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952361659
Diam. intérieur	15.875 mm
Diam. extérieur	22.225 mm
Épaisseur	12.7 mm
Poids	50 g
Conditionnement	1
Norme	Sans norme

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE