


## Douille à aiguilles BHAM1616-IKO - BHAM1616-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/douille/bham1616-iko>



Shaft dia. mm (inch)	Standard			Closed end			Mass (Ref.) g			Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g			
25.400 (1)	---	---	---	---	---	---	---	---	BHAM 1616 48	---	---

Boundary dimensions mm(inch)				Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring
F <sub>w</sub>	D	C	t <sub>1</sub> Max	Shaft dia. h8 Max.   Min.	Housing bore dia. J7 Max.   Min.	h <sub>s</sub>	h <sub>1</sub>				
25.400	33.338	25.40   1.000	3.4	25.400   25.387	33.352   33.327	26.400	44.500	15.000	IRB 1216		

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952362038
Diam. intérieur	25.4 mm
Diam. extérieur	33.338 mm
Épaisseur	25.4 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE