

Douille à aiguilles YB1816-IKO - YB1816-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/douille/yb1816-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
28.575 (1 1/8)	—	—	—	—	—	—	—	—	YB 1816 51.5
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	f_2	Shaft dia. h6	Housing bore dia. J7	C	C_0	rpm	
28.575 (1 1/8)	34.925 (1 3/8)	25.40 (1.000)	—	28.575 Max. 28.562 Min.	34.939 Max. 34.914 Min.	38 700 N	90 400 N	5 500	IRB 1416

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952362083
Diam. intérieur	28.575 mm
Diam. extérieur	34.925 mm
Épaisseur	25.4 mm
Poids	53 g
Conditionnement	-
Norme	Sans norme

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE