

Roulement conique NA558SW-552D-TIMKEN - NA558SW-552D-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/na558sw-552d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TNASW

TYPE TNASW

| Bearing Dimensions | | | | Load Ratings | | | | | | | |
|--------------------|---------|---------|---------------------------|-------------------------|-----------------------|-------------------------------------|-------------------------------------|-------------------------|-----------------------|------------------------|-------|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic C ₁₀ | Static C ₀ | Factor ¹⁾ Y ₁ | Factor ¹⁾ Y ₂ | Dynamic C ₉₀ | Static C ₀ | Factor ²⁾ K | |
| mm | in. | mm | mm | N | N | | | N | N | N | |
| 68.325 | 123.825 | 79.375 | 63.500 | 33200 | 74500 | 0.35 | 1.95 | 2.90 | 4900 | 2590 | 90180 |
| 2.700 | 4.875 | 3.125 | 2.500 | | | | | 1150 | 650 | 1940 | |

| Part Number | Inner | Outer | Dimensions | | | | Bearing Weight |
|-------------|-------|-------|--|--------------------------------------|--|--------------------------------------|----------------|
| | | | Max Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | |
| | mm | mm | mm | mm | mm | mm | kg |
| NA558SW | 950 | 3.5 | 76.8 | 1.5 | 115.8 | 4.33 | 4.33 |
| | | 0.14 | 3.02 | 0.06 | 4.53 | 0.17 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | TIMKEN |
| N° Ean13 | 3663952374673 |
| Diam. intérieur | 60.325 mm |
| Diam. extérieur | 123.825 mm |
| Épaisseur | 79.375 mm |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE