

Roulement à aiguilles GBR364828-IKO - GBR364828-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/gbr364828-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D_s Max.	$r_{as\ max}$
57.150 (2 1/4)	GBR 364828	580	57.150 (1) ₀	76.200 (3)	44.450 (1) ₀	69.2	1.5
Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾ n					
N	N	rpm					
133 000	276 000	2 500					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377568
Diam. intérieur	57.15 mm
Diam. intérieur	2 1/4" inch
Diam. extérieur	76.2 mm
Diam. extérieur	3" inch
Epaisseur	44.45 mm
Epaisseur	1 3/4" inch
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE