

Roulement à aiguilles GBR101812-IKO - GBR101812-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/gbr101812-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F	D	C	D_s Max.	$r_{as\ max}$
15.875 ($\frac{5}{8}$)	GBR 101812	55.5	15.875 $\frac{F_0}{0}$	28.575($\frac{1}{2}$)	19.050 $\frac{C_0}{0}$	24.5	0.6
Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾ n					
N	N	rpm					
23 500	28 500	9 500					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377698
Diam. intérieur	15.875 mm
Diam. extérieur	28.575 mm
Épaisseur	19.05 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE