

Roulement à aiguilles GBRI284824-IKO - GBRI284824-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/gbri284824-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
44.450 (1 1/2)	GBRI 284824	790	44.450 (1) $\frac{1}{2}$	76.200 (3)	38.100 (1) $\frac{1}{2}$	38.350	57.150 (2) $\frac{1}{2}$
Standard mounting dimensions mm		Sub-dynamic load rating C_0 N	Basic static load rating C_0 N	Allowable rotational speed (1) rpm	Assembled inner ring		
d_a Min.	d_a Max.				r_a Min.	r_a Max.	
52.5	55	69.2	1.5	113 000	224 000	2 500	LRBZ 283624

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377872
Diam. intérieur	44.45 mm
Diam. extérieur	76.2 mm
Épaisseur	38.1 mm
Poids	514 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE