


Roulement à aiguilles GBRI446828-IKO - GBRI446828-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/gbri446828-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
69.850 (2 3/4)	GBRI 446828	1 630	69.850 2 3/4	107.950 4 1/4	44.450 1 3/4	44.700	82.550 3 1/4

Standard mounting dimensions mm		Sub-dynamic load rating C_1 N	Basic static load rating C_0 N	Allowable rotational speed (1) rpm	Assembled inner ring LRBZ 445228		
d_a Min.	d_a Max.						
77	79	99.9	1.5	193 000	396 000	1 800	LRBZ 445228

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-applied. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952377957
Diam. intérieur	69.85 mm
Diam. extérieur	107.95 mm
Épaisseur	44.45 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE