

## Roulement à aiguilles RNA6912-UU-IKO - RNA6912-UU-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/rna6912-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring

| Shaft dia.<br>mm                         | Identification number |               |                   |               | Mass<br>(Ref.)<br>g | Boundary dimensions<br>mm |     |     |         |
|--|-----------------------|---------------|-------------------|---------------|---------------------|---------------------------|-----|-----|---------|
|  | With two seals        | With one seal | With two seals    | With one seal |                     | $F_w$                     | $D$ | $C$ | $r$ (*) |
| <b>68</b>                                | —                     | —             | <b>RNA 6912UU</b> | —             | 505                 | 68                        | 85  | 45  | 1       |
| Standard mounting diameter $D_s$ Max. mm | N                     | N             | N                 | N             |                     |                           |     |     |         |
| Basic dynamic load rating $C$            | 93 400                | 186 000       | 186 000           | 3 000         |                     |                           |     |     |         |
| Basic static load rating $C_0$           |                       |               |                   |               |                     |                           |     |     |         |
| Allowable rotational speed (rpm)         |                       |               |                   |               |                     |                           |     |     |         |

Notes: (\*) Minimum allowable value of chamfer dimension  $r$ . Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3663952379500 |
| Diam. intérieur | 68 mm         |
| Diam. extérieur | 85 mm         |
| Épaisseur       | 45 mm         |
| Conditionnement | 1             |

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE