

## Roulement à aiguilles NA6904-U-IKO - NA6904-U-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/na6904-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
20	—	—	—	—	NA 6904U	137	20	37	30	31

  

$r_s$ min	$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
		Min.	Max.	Max.				
0.3	25	22	24	35	33 000	44 600	7 500	LRTZ 202531

Notes: (1) Minimum allowable value of diameter dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381244
Diam. intérieur	20 mm
Diam. extérieur	37 mm
Épaisseur	31 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE