

## Roulement à aiguilles NA4907-U-IKO - NA4907-U-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/na4907-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
35	—	NA 4907U	—	—	179	35	55	20	21

  

$r_s$ min ( <sup>1)</sup> )	$F_w$	Standard mounting dimensions (mm)				Basic dynamic load rating C N	Basic static load rating $C_0$ N	Allowable rotational speed( <sup>2)</sup> ) rpm	Assembled inner ring
		Min.	Max.	$d_s$	$D_s$				
0.6	42	39	41	51	30 100	46 300	4 500	LRTZ 354221	

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381466
Diam. intérieur	35 mm
Diam. extérieur	55 mm
Épaisseur	21 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE