

Roulement à aiguilles NA6912-U-IKO - NA6912-U-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/na6912-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		ϕ	d	D	C
60	—	—	—	NA 6912U	785	60	85	45	46

r_s min	F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
		d_s Min.	d_s Max.	D_s Max.				
1	68	65	66	80	93 400	186 000	3 000	LRTZ 608846

Notes: (1) Minimum allowable value of shaft diameter r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381671
Diam. intérieur	60 mm
Diam. extérieur	85 mm
Épaisseur	46 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE