

Roulement à aiguilles NA4915-U-IKO - NA4915-U-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/na4915-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
75	—	NA 4915U	—	—	815	75	105	30	31

r _s min ⁽¹⁾	F _w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		d _s Min.	d _s Max.	D _s Max.				
1	85	80	83	100	79 600	153 000	2 000	LRTZ 758531

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381787
Diam. intérieur	75 mm
Diam. extérieur	105 mm
Épaisseur	31 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE