

Roulement à aiguilles NA4919-UU-IKO - NA4919-UU-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/na4919-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.)	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		α	d	D	C
95	NA 4919UU				1 420	95	130	35	36

r_s mm	F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
		Min.	Max.					
1.1	110	101.5	108	123.5	109 000	250 000	1 700	LRTZ 9511036

Notes: (1) Minimum allowable value of shaft diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952381930
Diam. intérieur	95 mm
Diam. extérieur	130 mm
Épaisseur	36 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE