

Roulement à aiguilles BRI223520-U-IKO - BRI223520-U-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/bri223520-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		g	d	D	C	B
34.925 (1 $\frac{3}{8}$)		BRI 223520 U	275	34.925 (1 $\frac{3}{8}$)	55.562 (2 $\frac{1}{4}$)	31.750 (1 $\frac{1}{4}$)	32.000	
F_w	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
	Min.	Max.	$r_{as max}$ ⁽¹⁾					
	40.2	40.2	48.3	0.6	44 800	70 900	4 500	LRBZ 222620 B

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952382630
Diam. intérieur	34.925 mm
Diam. extérieur	55.562 mm
Épaisseur	31.75 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE