

## Roulement à aiguilles GBR526828-U-IKO - GBR526828-U-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/gbr526828-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$F_w$	$D$	$C$
<b>82.550</b> (3 1/4)	<b>GBR 526828 U</b>		960	82.550 (3 1/4)	107.950 (4 1/4)	44.450 (1 3/4)
Standard mounting dimensions mm		Ball dynamic load rating $C_1$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup>		
$D_A$	$r$ as max	N	N	rpm		
Max.	1.5	127 000	231 000	950		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952383187
Diam. intérieur	82.55 mm
Diam. extérieur	107.95 mm
Épaisseur	44.45 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE