


## Roulement à aiguilles NAU4908-UU-IKO - NAU4908-UU-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/nau4908-uu-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings [With Seal]  
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r <sub>1 min</sub> (*)	J
40	—	NAU 4908UU	220	40	62	22	0.6	46
	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed (1) rpm					
56	23 400	29 400	4 000					

Notes: (\*) Minimum allowable value of chamfer dimension r  
(1) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAU and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386027
Diam. intérieur	40 mm
Diam. extérieur	62 mm
Épaisseur	22 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE