


Roulement à aiguilles NAU4918-UU-IKO - NAU4918-UU-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/nau4918-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾	J
90	—	NAU 4918UU	1 210	90	125	35	1.5	101
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
115.5	N 79 500	N 130 000	rpm 1 900					

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386539
Diam. intérieur	90 mm
Diam. extérieur	125 mm
Épaisseur	35 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE