


## Roulement à aiguilles NAS5012-UU-NR-IKO - NAS5012-UU-NR-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/nas5012-uu-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
60	NAS 5012UU	NR	1.20	60	95	99.8	46	45	34	5.5

f	c	r <sub>s</sub> mm <sup>(1)</sup>	J <sub>r</sub>	Basic dynamic load rating C <sub>r</sub> N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm
2.5	2	0.6	73	123 000	208 000	1 700

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r<sup>(1)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
Remarks: 1. The bearings with seals are provided with prepacked grease.  
2. The bearings with seals are provided with prepacked grease.

### CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952386812
Diam. intérieur	60 mm
Diam. extérieur	95 mm
Épaisseur	46 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE