

Roulement à aiguilles NAS5088-ZZ-IKO - NAS5088-ZZ-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/nas5088-zz-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



| Shaft dia. mm | Identification number | | Mass (Ref.) kg | Boundary dimensions mm | | | | | | |
|---------------|-----------------------|-------------|----------------|------------------------|-----|----------------|-----|-----|----------------|---|
| | Sealed type | Shield type | | d | D | D ₂ | B | C | C ₁ | S |
| 440 | | NAS 5088ZZ | 310 | 440 | 650 | — | 280 | 278 | — | — |

| f | c | r _s mm ⁽¹⁾ | J _r | Basic dynamic load rating C _r N | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm |
|---|---|----------------------------------|----------------|--|---|---|
| — | 8 | 3 | 516 | 4 570 000 | 10 900 000 | 200 |

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3663952387413 |
| Diam. intérieur | 440 mm |
| Diam. extérieur | 650 mm |
| Épaisseur | 280 mm |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE