

## Roulement à aiguilles NBXI1425Z-IKO - NBXI1425Z-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/nbxi1425z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification Number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
14					<b>NBXI 1425Z</b>	72.5	14	26	30

  

Boundary dimensions mm				Lead-in chamfer radius mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring LRT 141717
D <sub>2</sub>	L	B	H			Radial	Radial		
31	25	17	9	8	12 900	11 400	16 300	28 600	13 000

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952390758
Diam. intérieur	14 mm
Diam. extérieur	26 mm
Épaisseur	25 mm
Poids	50 g
Conditionnement	-
Norme	Sans norme

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE