

Roulement à aiguilles NBXI4535-IKO - NBXI4535-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/nbxi4535-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification Number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
45	---	---	---	NBXI 4535	366	---	45	62	70

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 455025		
D ₂	L	B	H			Radial	Radial			Axial	
71.5	35	25	14	10	49	42 200	43 300	83 400	148 000	5 000	LRT 455025

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remark: The outer ring has an oil groove and an oil hole.
Z: Grease is not prepacked. Perform proper lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952391021
Diam. intérieur	45 mm
Diam. extérieur	62 mm
Épaisseur	35 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE