

Rotule GE SB85A-IKO - SB85A-IKO

<https://www.123roulement.ca/roulement-palier/rotule/ge/sb85a-iko>

SPHERICAL BUSHINGS
steel Spherical Bushings

Identification number	Mass (Ref.)	Boundary dimensions mm						Per titi c
		d	D	B	C	d _k	r _{s min} (°)	
SB 85A	4.29	85	135	74	63	125	0.6	

Mounting dimensions mm			Dynamic load capacity C _d	Static load capacity C _s
Max. (°)	Max.	Min.		
100.5	130.5	116	772 000	4 630 000

Minimum allowable value of chamfer dimensions r₁ and r₂
When Spherical Bushings are used with full fitting angle, the shaft shoulder dimension must be less than the maximum vs.
The inner ring and the outer ring have an oil groove and two oil holes, respectively.
Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952391465
Diam. intérieur	85 mm
Diam. intérieur	3.346" inch
Diam. extérieur	135 mm
Diam. extérieur	5.315" inch
Epaisseur	74 mm
Epaisseur	2.913" inch
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE