

Rotule GE GE70EC-2RS-IKO - GE70EC-2RS-IKO

<https://www.123roulement.ca/roulement-palier/rotule/ge/ge70ec-2rs-iko>

IKO
SPHERICAL BUSHINGS
Maintenance-free Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_k	r_1 mm ⁽¹⁾	r_2 mm ⁽¹⁾	α	α_1
70	—	GE 70EC-2RS	1.54	70	105	49	40	92	1	1	—	4
Mounting dimensions mm			DynamiC load capacity C_d	Static load capacity C_s								
d_s		D_s	Min.	Max.	Min.	Max.						
Min.	Max. ⁽²⁾	Max.	Min.	Max.	N	N						
75.5	77.5	99.5	91	361 000	902 000							

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
 Remark No oil hole is provided.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952393230
Diam. intérieur	70 mm
Diam. extérieur	105 mm
Épaisseur	49 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE