


Rotule GE GE110ES-IKO - GE110ES-IKO

<https://www.123roulement.ca/roulement-palier/rotule/ge/ge110es-iko>

IKO

SPHERICAL BUSHINGS

Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾ r _{1s} min	r ₂ ⁽¹⁾ r _{2s} min	α	α ₁
110	GE 110ES		4.94	110	160	70	55	140	1	1	6	4
Mounting dimensions mm		Dynamic load capacity C _d		Static load capacity C _s								
d _s	D _s											
Min.	Max. ⁽²⁾	Max.	Min.	N		N						
115.5	121	154.5	138	755 000		4 530 000						

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
 Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
 2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952393773
Diam. intérieur	110 mm
Diam. extérieur	160 mm
Epaisseur	70 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE