


Rotule GE GE70GS-IKO - GE70GS-IKO

<https://www.123roulement.ca/roulement-palier/rotule/ge/ge70gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾	r ₂ ⁽¹⁾	α	α ₁
70	GE	70GS	3.00	70	120	70	45	105	1	1	16	14

Mounting dimensions mm				Dynamic load capacity C _d N	Static load capacity C _s N
d _s		D _s			
Min.	Max. ⁽²⁾	Max.	Min.		
75.5	78	114.5	103	463 000	2 780 000

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952393780
Diam. intérieur	70 mm
Diam. extérieur	120 mm
Épaisseur	70 mm
Type	GE
Lubrification	sans
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE