


## Roulement conique 32928-JR-JTEKT - 32928-JR-KOYO

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/32928-jr-koyo>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
140	190	32	32	25	206	390	1 800	2 300	32928JR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.	Constant e	Axial load factors Y <sub>1</sub>	Axial load factors Y <sub>0</sub>	(Refer. 1) Mass (kg)	
2CC	33.6	150	150	181	174	184	6	7	2	1.5	0.36	1.67	0.92	2.57

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250125683
Diam. intérieur	140 mm
Diam. extérieur	190 mm
Épaisseur	32 mm
Poids	2500 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE