

Roulement conique 30228-JR-JTEKT - 30228-JR-KOYO

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/30228-jr-koyo>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
140	250	45.75	42	36	420	570	1 500	1 900	30228JR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _α min.	d _α max.	D _α min.	D _α max.	S _α min.	S _α max.		r _α min.	r _α max.		Y ₁	Y ₀	
4FB	49.4	158	163	236	219	237	9	9.5	3	2.5	0.44	1.38	0.76	8.97

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952419763
Diam. intérieur	140 mm
Diam. extérieur	250 mm
Épaisseur	45.75 mm
Poids	8989 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE