

Galet de came avec axe CF8-UUM-IKO - CF8-UUM-IKO

<https://www.123roulement.ca/roulement-palier/roulement-bille/galet-came-axe/cf8-uum-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot

CF-UU

Stud dia. mm	Identification number				Mass (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
8					28.5	19	11	8	M 8×1

Boundary dimensions mm													
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	f _{max} (°)	f Min. mm	Maximum ignoring torque N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N
10	12.2max	32.2max	20	—	0.6	*4	—	0.3	13	7.1	4 250	4 740	4 620

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952441061
Diam. intérieur	8 mm
Diam. intérieur	0.315" inch
Diam. extérieur	19 mm
Diam. extérieur	0.748" inch
Epaisseur	11 mm
Epaisseur	0.433" inch
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE