


Galet de came avec axe CFES12-UU-IKO - CFES12-UU-IKO

<https://www.123roulement.ca/roulement-palier/roulement-bille/galet-came-axe/cfes12-uu-iko>

IKO
CAM FOLLOWERS
Solid Eccentric Stud Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d ₁
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
12				CFES 12 UU	95	30	14	12

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N·m	Back dynamic load rating C N	Back static load rating C ₀ N	Maximum allowable static load N	
G	G ₁	B _{max}	B _{1 max}	B ₂	B ₃	C ₁	B ₁	B ₂	α ₂						
M12×1.5	13	15.2	40.2	25	6	0.6	6	3	0.6	0.4	21	21.9	7 910	9 790	9 790

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060459220
Diam. intérieur	12 mm
Diam. extérieur	30 mm
Épaisseur	14 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE