

Galet de came avec axe CFE24-V-IKO - CFE24-V-IKO

<https://www.123roulement.ca/roulement-palier/roulement-bille/galet-came-axe/cfe24-v-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric axle mm	Identification number				Mass (Ref.) g	D	C	d _e
	Shield type		Sealed type					
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33	CFE 24 V				900	62	29	33

Boundary dimensions mm														
G	B ₃	B _{max}	B ₁ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	Eccentricity E	Mounting diameter f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M24 × 1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	46 800	92 000	52 000

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060461247
Diam. intérieur	33 mm
Diam. intérieur	1.299" inch
Diam. extérieur	62 mm
Diam. extérieur	2.441" inch
Epaisseur	29 mm
Epaisseur	1.142" inch
Poids	900 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE