


Galet de came avec axe CF-FU1-20-IKO - CF-FU1-20-IKO

<https://www.123roulement.ca/roulement-palier/roulement-bille/galet-came-axe/cf-fu1-20-iko>

IKO

CAM FOLLOWERS

Centralized Lubrication Type Cam Followers With Cage/With Screwdriver Slot



CF-FU1

| Stud dia. mm | Identification number | | Mass (Ref.) g | Boundary dimensions mm | | | | |
|-----------------|----------------------------|--------------------------------|---------------------|------------------------|----|----------------|-----------|----------------|
| | With crowned outer ring | With cylindrical outer ring | | D | C | d ₁ | G | G ₁ |
| 20 | | CF-FU1-20 | 460 | 52 | 24 | 20 | M20 x 1.5 | 21 |

| B _{max} | B _{1max} | B ₂ | B ₃ | C ₁ | g ₂ | M ₁ | M ₂ | f _g min ⁽¹⁾ | Mounting dimension f _g mm | Maximum tightening torque N-m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load N |
|------------------|-------------------|----------------|----------------|----------------|----------------|----------------|----------------|-----------------------------------|---|--|--|--|--|
| 25.6 | 66.1 | 40.5 | 9 | 0.8 | 4 | PT 1/8 | PT 1/8 | 1 | 34 | 119 | 20 700 | 34 600 | 34 600 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | IKO |
| N° Ean13 | 3616060461681 |
| Diam. intérieur | 20 mm |
| Diam. extérieur | 52 mm |
| Épaisseur | 24 mm |
| Poids | 460 g |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE