


## Galet de came avec axe CR10-B-IKO - CR10-B-IKO

<https://www.123roulement.ca/roulement-palier/roulement-bille/galet-came-axe/cr10-b-iko>

IKO  
**CAM FOLLOWERS**  
Inch Series Cam Followers With Cage/With Hexagon Hole



| Stud dia.<br>mm<br>(inch)   | Identification number      |                                |                            |                                | Mass<br>(Ref.)<br>g | D                     | C                    | d <sub>1</sub>                                | G<br>UNF                                  | G <sub>1</sub>                                     |   |
|-----------------------------|----------------------------|--------------------------------|----------------------------|--------------------------------|---------------------|-----------------------|----------------------|---|---|--|---|
|                             | Shield type                |                                | Sealed type                |                                |                     |                       |                      |   |   |  |   |
|                             | With covered<br>outer ring | With cylindrical<br>outer ring | With covered<br>outer ring | With cylindrical<br>outer ring |                     |                       |                      |   |   |  |   |
| <b>6.350</b><br>(.250)      | <b>CR 10 B</b>             |                                |                            |                                | 19                  | 15.875 $\frac{5}{16}$ | 10.319 $\frac{3}{8}$ | 6.350 $\frac{1}{4}$                           | $\frac{1}{4}$ -28                         | 7.938 $\frac{5}{16}$                               |   |
| Boundary dimensions mm/inch |                            |                                |                            |                                |                     |                       |                      |   |   |  |   |
| B<br>max                    | B <sub>2</sub>             | B <sub>3</sub>                 | C <sub>1</sub>             | E <sub>1</sub>                 | E <sub>2</sub>      | H                     | r                    | Bearing<br>dimension<br>f<br>M/m<br>(mm/inch) | Maximum<br>ignoring<br>torque<br>C<br>N-m | Basic static<br>load rating<br>C <sub>0</sub><br>N | Basic dynamic<br>load rating<br>C <sub>0</sub><br>N |
| 11.8148                     | 15.875 $\frac{5}{16}$      | - (-)                          | 0.794 $\frac{1}{16}$       | - (-)                          | - (-)               | 3.175 $\frac{1}{8}$   | 0.207 $\frac{1}{20}$ | 11.508 $\frac{9}{16}$                         | 2.4                                       | 3 650  | 3 670   |

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | IKO           |
| N° Ean13        | 3616060462343 |
| Diam. intérieur | 6.35 mm       |
| Diam. extérieur | 15.875 mm     |
| Épaisseur       | 10.319 mm     |
| Poids           | 19 g          |
| Conditionnement | 1             |

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE