


Galet de came avec axe CR14-B-IKO - CR14-B-IKO

<https://www.123roulement.ca/roulement-palier/roulement-bille/galet-came-axe/cr14-b-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers With Cage/With Hexagon Hole



CR14-B

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type		Sealed type								
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
9.525 ($\frac{3}{8}$)	CR 14 B				46	22.225 ($\frac{7}{8}$)	12.700 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	$\frac{1}{4}$ -24	9.525 ($\frac{3}{8}$)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm (mm/inch)	Maximum ignoring torque C N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N
14.2 (0.56)	22.225 ($\frac{7}{8}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	2.381 ($\frac{1}{8}$)	4.762 ($\frac{3}{16}$)	0.794 ($\frac{1}{32}$)	15.081 ($\frac{5}{8}$)	10.8	4 790	5 910

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462459
Diam. intérieur	9.525 mm
Diam. extérieur	22.225 mm
Épaisseur	12.7 mm
Poids	46 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE