


Galet de came avec axe CR12-R-IKO - CR12-R-IKO

<https://www.123roulement.ca/roulement-palier/roulement-bille/galet-came-axe/cr12-r-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type		Sealed type							
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring						
9.525 ($\frac{3}{8}$)	CR 12 R				35	19.050 $\frac{3}{4}$	12.700 $\frac{1}{2}$	9.525 $\frac{3}{8}$	G ₁ -24	9.525 $\frac{3}{8}$
Boundary dimensions (mm/inch)										
B _{max}	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm/inch	Maximum tightening torque C N·m	Basic dynamic load rating C ₀ N	Basic static load rating C ₀ N
14.2 0.56	22.225 $\frac{7}{8}$	6.350 $\frac{1}{4}$	0.794 $\frac{1}{32}$	4.762 $\frac{3}{16}$	2.381 $\frac{3}{32}$	0.794 $\frac{1}{32}$	13.464 $\frac{1}{2}$	10.8	4 420	5 110

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060462848
Diam. intérieur	9.525 mm
Diam. extérieur	19.05 mm
Épaisseur	12.7 mm
Poids	35 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE