


Galet de came avec axe CR30-V-IKO - CR30-V-IKO

<https://www.123roulement.ca/roulement-palier/roulement-bille/galet-came-axe/cr30-v-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



CR-V

Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type With cover With cylindrical outer ring		Sealed type With cover With cylindrical outer ring		ϕ	D	C	d_1	G UNF	G_1
19.050 ($\frac{3}{4}$)	CR 30 / V				418	47.625 ($1 \frac{7}{8}$)	25.400 (1)	19.050 ($\frac{7}{8}$)	$\frac{1}{4}$ -16	22.225 ($\frac{7}{8}$)
Boundary dimensions: mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N		
B max	B_2	B_3	C_1	g_1					g_2	r
25.8 (1.00)	44.650 (1 $\frac{7}{8}$)	11.112 ($\frac{1}{2}$)	0.794 ($\frac{1}{4}$)	4.762 ($\frac{1}{4}$)	3.969 ($\frac{1}{4}$)	1.588 ($\frac{1}{4}$)	32.543 (1 $\frac{1}{4}$)	100	35 300	55 800

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060464101
Diam. intérieur	19.05 mm
Diam. extérieur	47.625 mm
Epaisseur	25.4 mm
Poids	418 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE