


## Galet de came avec axe CR30-VBUU-IKO - CR30-VBUU-IKO

<https://www.123roulement.ca/roulement-palier/roulement-bille/galet-came-axe/cr30-vbuu-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR30-VBUU

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Sealed type With cover outer ring	Sealed type With cylindrical outer ring							
19.050 ( $\frac{3}{4}$ )			CR 30	VBUU	418	47.625 ( $\frac{1}{2}$ )	25.400 ( $\frac{1}{2}$ )	19.050 ( $\frac{3}{4}$ )	7-16	22.225 ( $\frac{7}{8}$ )	
Boundary dimensions mm(inch)											
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	H	r	Mounting dimension f Min. mm(inch)	Maximum spinning torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
25.8106	44.450 ( $\frac{1}{2}$ )	11.112 ( $\frac{1}{2}$ )	0.794 ( $\frac{1}{8}$ )	4.792 ( $\frac{3}{8}$ )	3.969 ( $\frac{1}{4}$ )	7.938 ( $\frac{1}{2}$ )	1.588 ( $\frac{1}{8}$ )	32.543 ( $\frac{1}{2}$ )	100	35 300	55 600

## CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060464163
Diam. intérieur	19.05 mm
Diam. extérieur	47.625 mm
Épaisseur	25.4 mm
Poids	418 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE