


## Roulement à rouleaux NQ24-12-JTEKT - NQ24-12-KOYO

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nq24-12-koyo>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$C_r$	$C_{10}$	Oil lub.	Without inner ring	
24	20	32	12	9.6	14.4	19 000	NQ24/12	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
	$d_i$	$D_i$	$r_i$	0.025	0.038			
	max.	max.	max.					
	22	30	0.3					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482293
Diam. intérieur	24 mm
Diam. extérieur	32 mm
Épaisseur	12 mm
Poids	25 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE